



6000A Rackmountable Card Cage

3 RU high enclosure with 20 positions for any combination of Fiberlink card modules. Power supply and alarm sensing module available.



| Part # | Description | Slots in Cage |
|--------|--------------|---------------|
| 6000A | Card Cage | 20 |
| 6010A | Power Supply | 3 |
| 6020A | Alarm Module | 1 |

Features

Rackmountable 19" card cage offers 20 positions for any combination of Fiberlink transmitter, receiver and transceiver card modules. (Please refer to the Fiberlink® products' data sheet for slot and power requirements)

Cage may be powered with optional 3-position plug-in power supply or with an external, customer-provided power source

Two power supplies may be used to provide redundant power

Optical signal input and output connectors on each card module are at the rear of the card cage

Optional alarm module indicates fault condition via an audible piezo sounder, blinking red LED and activation of isolated contacts for use with remote monitoring

Single and multiple position blank filler panels are available to conceal positions not in use

ROHS Compliant

Ordering Information

| Part Number | Description | Number of Positions |
|-------------|----------------------------------|---------------------|
| 6000A | Rackmountable Card Cage | 20 |
| 6010A-pp | Universal Switching Power Supply | 3 |
| 6020A | Alarm Sensing Module | 1 |
| 6031 | Single Filler Panel | 1 |
| 6032 | Double Filler Panel | 2 |
| 6034 | Quadruple Filler Panel | 4 |

Power Supply Suffix Codes (pp) for AC Line Cord:

| | | |
|--------------------|---------------------|-------------|
| NA - North America | AU - Australia | EU - Europe |
| JP - Japan | UK - United Kingdom | |

About CSI

Communications Specialties, Inc. (CSI) is an award-winning manufacturer of Pro A/V products for the distribution, conversion or transmission of television and computer video signals, including fiber optic transmission systems, scan converters and video scalars. The company was founded in 1983 by veterans of the broadcast industry. Since then, CSI has managed to consistently design innovative products that are used worldwide by Fortune 500 Companies in a variety of markets such as Broadcast/Professional A/V, Videoconferencing, Education, Home Theater, Security, ITS, Industrial Monitoring, and more!

Also from CSI: Scan Do® Scan Converters and Deuce® Video Scalars

Sales



CSI Communications Specialties, Inc.

631-273-0404 | commspecial.com
info@commspecial.com

Card Cage Specifications:

| | |
|----------------------------------|---|
| Total Number of Positions | 20 |
| Finish | Clear, irridited aluminum |
| Physical Size | 19 W x 5.25 H x 11 D (inches) 483 W x 133 H x 280 D (mm) |
| Operating Temperature Range | -35 to +75° C |
| Optional External Power Input* | 8.7 to 12 VDC |
| Max. Allowable External Current* | 11 amperes |
| External Power Input Connector | 3 position terminal block |

*The external power input connector is reverse-polarity protected but should be current limited and/or fused so that input current cannot exceed a maxium of 11 amperes

Universal Switching Power Supply Specifications:

| | |
|----------------------------------|--|
| Total Number of Positions | 3 |
| Input Voltage Range (continuous) | 90 to 260 volts AC 47/63 Hz @ 2A max. |
| Output Power | 8.0 volts DC +/-1% regulated @ 11 A max. |
| Output Protection | Overvoltage; crowbar, short circuit; current limiting |
| Input Protection | P/C fuse for catastrophic failure |
| Ripple and Noise | 1% p-p, DC to 20 MHz |
| Operating Temperature Range | -35 to +75 degrees C |
| EMI compliance | FCC 20870 Class B EN 55022 Class B |
| Safety Compliance | CSA 22.3 No. 220, VDE EN 60 950, European CE |
| Input Power Connector | IEC 320 |

Alarm Sensing Module Specifications:

| | |
|---------------------------|---|
| Total Number of Positions | 1 |
| Alarm Indications* | Blinking red LED, pulsing piezo sounder, external SPDT contact closures |
| External Contact Ratings | 115/230 VAC 50/60 Hz 5 amperes resistive |

* Note that the audible piezo sounder can be turned off via a front panel switch. The blinking red alarm LED and the activated external contacts cannot be deactivated until the fault condition is corrected.



6000A Card Cage



Schedule
Contract GS-03F-5063C



Want to learn more about fiber?

Log on to commspecial.com
for fiber related resources written
for Pro A/V Professionals by
Pro A/V Professionals!



Backed by a 30-day satisfaction
guarantee and a three-year limited
warranty on parts and labor.
See website for terms and conditions.

Sales



CSI Communications
Specialties, Inc.

631-273-0404 | commspecial.com
info@commspecial.com

UPDATED 2/4/2009

All specifications subject to change without notice. © 2009

Fiberlink and the starburst logo are registered trademarks of
Communications Specialties, Inc. CSI and the triangle designs
are trademarks of Communications Specialties, Inc.

