

PU-513L-KIT New Product

v1.4 HDMI over Single CAT5e/6 HDBaseT™ LITE Extender Kit



The PU-513L-KIT allows uncompressed HDMI, IR and RS-232 signals to be transmitted over a Single CAT5e/6 cable to distances of up to 60m.

FEATURES

- HDMI 1.4 with 3D, 4Kx2K support, HDCP and DVI compliant
- Supports HDMI 1.4 (including HDCP) over a single CAT5e/6 up to 60m
- Complies with HDBaseT™- Lite specifications
- Full HD resolution support (1080p@60Hz/36-bit), 3D over 60m, 4Kx2K over 40m and PC resolution support (VGA to WUXGA) over CAT5e/6 cable
- HDMI input up to 15m with 8-bit deep colour, or 10m with 12-bit deep colour
- Supports HDMI output up to 15m with 8/12-bit deep colour
- Supports IR and RS-232 Control
- Supports High Definition LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus and DTS-HD Master Audio transmission

SPECIFICATIONS

PU-513LTX

Inputs:	1x HDMI (1x HDMI Uncompressed AV and Data), 1x 3.5mm Stereo mini-jack (1x RS-232)
Outputs:	1x RJ45 (1x HDMI & Propriety Data) 1x 3.5mm Stereo mini-jack (1x Infra Red Emitter)
Power:	5V/2.6A US/EU standards, CE/FCC/UL certified)
Dimensions:	52mm (W) x 52mm (D) x 18mm (H)
Net Weight:	60g

PU-513LRX

Inputs:	1x RJ45 (1x HDMI & Propriety Data) 1x 3.5mm Stereo mini-jack (1x Infra Red Receiver)
Outputs:	1x HDMI (1x HDMI Uncompressed AV and Data), 1x 3.5mm Stereo mini-jack (1x RS-232))
Power:	5V/2.6A US/EU standards, CE/FCC/UL certified)
Dimensions:	54mm (W) x 54mm (D) x 20mm (H)
Net Weight:	60g
Gross Weight:	840g
Packaging:	Boxed

