




## Icron USB and KVM Extender Solutions

All Icron extender solutions include the ExtremeUSB® suite of features such as transparent USB extension, true plug and play (no software drivers), and compatibility with Windows®, macOS™, Linux® and Chrome OS™ operating systems. A complete system includes a LEX (Local Extender), a REX (Remote Extender) and a power adapter if required.

	USB Type	USB Extender Model	Max. Distance	Transmission Media		Power Adapter Location	USB Port(s)
Video + USB Extenders	3.1 Gen 1	USB 3-2-1 Raven™ 3124	200m	Multimode Fiber		LEX and REX	4
	3.2 Gen 1	USB 3-2-1 Raven™ 3104 Pro	100m	CAT 6a/7		LEX and REX	4
	3.1 Gen 1	USB 3-2-1 Raven™ 3104	100m	CAT 6a/7		LEX and REX	4
	3.0	USB 3.0 Spectra™ 3022 <sup>①</sup>	100m <sup>2</sup>	Multimode Fiber		REX	2
	3.0	USB 3.0 Spectra™ 3001-15 <sup>①</sup>	15m	Active Copper Cable		Bus Powered	1
	2.0	USB 2.0 Ranger® 2344	10km	Singlemode Fiber		REX	4
	2.0	USB 2.0 Ranger® 2324	500m	Multimode Fiber		REX	4
	2.0	USB 2.0 Ranger® 2312	100m	CAT 5e/6/7		LEX or REX	2
	2.0	USB 2.0 Ranger® 2311	100m	CAT 5e/6/7		LEX or REX	1
	2.0	USB 2.0 Ranger® 2304GE-LAN <sup>®</sup>	100m	CAT 5e/6/7 or LAN		REX	4
	2.0	USB 2.0 Ranger® 2304	100m	CAT 5e/6/7		REX	4
	2.0	USB 2.0 Ranger® 2301GE-LAN <sup>③</sup>	100m	CAT 5e/6/7 or LAN		REX	1
	2.0	USB 2.0 Ranger® 2301	100m	CAT 5e/6/7		REX	1
	1.1	USB 1.1 Rover® 2850	85m <sup>@</sup>	CAT 5e/6/7		Bus Powered	2
	1.1	USB 1.1 Rover® 1850	85m <sup>④</sup>	CAT 5e/6/7		Bus Powered	1
	USB Throughput	KVM Extender Model	Max. Distance	Transmission Media	V	ideo Type and ax. Resolution	USB Port(s)
	40Mbps	EL5353 DVI + USB 2.0	100m	CAT 5e/6/7		/I Uncompressed 1920 x 1200	3
	40Mbps	EL5363 HDMI + USB 2.0	100m	CAT 5e/6/7		MI Uncompressed , 1080p, 1920 x 1200	3

 $<sup>\</sup>stackrel{\textcircled{\scriptsize 0}}{\bigcirc}$  USB 3.0 Spectra extenders are not backward compatible with USB 2.0 and 1.1 devices.

<sup>(4)</sup> Up to 40m is achievable for all USB devices; 85m is achievable for most low-powered HID USB devices.



The maximum distance is 50m with storage type USB 3.0 devices; 100m or more is achievable when using USB 3.0 bulk traffic cameras.

<sup>®</sup> Works over a LAN although does not support SwitchableUSB™ protocol.



## **Market Applications**

USB has become the de facto standard for computer peripheral connectivity spanning broad markets and applications. However, many applications are challenged by USB's distance limitation of five meters for USB 2.0 and approximately three meters for USB 3.1/3.0, where the host computer needs to be located beyond these distances from the user. Icron's ExtremeUSB® extender solutions bridge the gap with simple plug and play installation and compatibility with all major operating systems.



Web conferencing and audio extension Room reservations over corporate LAN Video matrix switching




Post production editing Mobile production truck Remote storage



Machine Vision Kiosk controls and sensors Robotics



Store directories Interactive menus Point of purchase displays



Education
Interactive whiteboards and touchscreens
Virtual reality learning

USB audio extension



Command and control centers Remote stations Device Class Filtering



CT Scan and MRI machines Patient monitoring Remote record access



Well-head flow monitoring Asset management Data logging and intrusion alarming

For more information, please contact Icron at IcronSales@MaximIntegrated.com.